

PM 20 (910 511)

- Combined testing of protective circuits with gas discharge tubes, varistors and Zener diodes
- Easy and flexible use
- For use with PA BXT and PA DRL test adapters



Figure without obligation

Combined device for testing the sparkover voltage of surge arresters (with gas discharge tubes / varistors / Zener diodes). Storage bag and measuring accessories included.

| Type | PM 20 |
|---|--|
| Part No. | 910 511 |
| Nominal voltage (d.c.) (U_N) | 8-12 V d.c. |
| Test parameter: Test voltage | max. 1200 V d.c. |
| Test parameter: Test current (reference voltage) | 1 mA d.c., constant |
| Measured value indication | alphanumeric, eight-digit LCD |
| Test output sockets | safety pole terminals (4 mm), positive pole: red colour, negative pole: black colour |
| Testing period | ≤ 1.5 sec. |
| Number of individual tests during battery operation | typically 2000 |
| Accessories included in delivery | 2 test leads (each 1 m long), 2 safety tapping test clips, 1 plug-in power supply unit (230 V a.c.), 1 storage bag |
| Dimensions of the storage bag | 300 x 110 x 110 mm |
| Weight | 1,32 kg |
| Customs tariff number (Comb. Nomenclature EU) | 90308900 |
| GTIN | 4013364111424 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.